

Network Laboratory

Distributed Spectrum Sensing using Software-Defined Radio

Felipe Loose, Philip Chan, Matthew D'Angiolillo, Joseph Azzolini, Vidur Nayyar

Advisors: Ivan Seskar, Roy D. Yates

Summer Internship 2014


Motivation

To improve conventional wireless communication and allow better usage of the electromagnetic spectrum by sensing the frequency content in the environment and avoiding interference between users.

Objectives

□Project Goal:

1. To be able to detect a (randomly generated) signal from a transmitter using multiple receivers (Fig. 1).



USRPD

- □ USRPD (Universal Software Radio Peripheral Daemon) [1] is a software package, created by Dragoslav Stojadinovic, designed to work with spectrum sensing using multiple transmitters and receivers (Fig 2).
- ☐ Receivers are able to communicate with a central controller and perform various functions.
- ☐ USRPD is used to obtain and process data acquired by energy calculations performed on the spectrum.




Fig. 2 - Logic diagram for USRPD [1].

Spectrum Sensing via Energy Detection

- ☐ Energy detection was used to locate the signal, as seen in the block diagram below (Fig. 3);
- ☐ The USRP hardware performs initial filtering and converts the signal into digital samples [3];
- ☐ A Fast Fourier Transform is performed on the samples in the USRPD program




Fig. 3 - Energy detection block diagram [2],[3].

Results

☐ Graphical User Interface Design

☐ Designed a MATLAB Graphical User Interface to create a spectrogram for visualization (Fig. 3);




Fig. 4 - Spectrogram Results

Results (continued)

☐ USRPD Controller Program

☐ Designed and implemented a controller program to send commands and get data from multiple nodes using USRPD (Fig. 5);




Fig. 5 - USRPD Controller diagram

Future Work

- ☐ Develop a method to compare different sensing algorithms
- ☐ Configure our control program to display results in real time.
- ☐ Allow for user-inputted sensing algorithms.

References

- [1] Dragoslav Stojadinovic. USRPD user guide available at http://wiser.orbit-lab.org/wiki/wiser/mSoftware/gWiserd#wiserd.
- [2] Sun, Hongjian, et al. "Wideband Spectrum Sensing for Cognitive Radio Networks: A Survey." IEEE Wireless Communications (April 2013): 74-81. Web.
- [3] Department of Electrical and Computer Engineering. "ECE4305: Software-Defined Radio Systems and Analysis, Laboratory 4". Lab handbook. Worcester Polytechnic Institute. Worcester, MA. 2011. Web.

Project website: https://www.sites.google.com/site/winlabss/ Project github: https://github.com/PhilipRChan/USRPD_Control/

